


## SSF SIPLACE® Compatible Tape Feeders



**Compatible with SIPLACE® family placement machines, Hover-Davis SSF feeders are specifically designed to enhance line operation and productivity.**

### Features:

- Plug & Play compatibility
- Durable, ergonomic construction
- Quick and easy tape loading
- Modular design, user serviceable
- Reliable electronic tape indexing
- Reverse index tape drive
- Simple, electronic pick point adjustment and calibration
- Feeder status indicator
- Large capacity tape reservoir
- On-board diagnostics
- Comprehensive 2 year warranty

### Benefits:

- Improve pick rates
- Reduce loading time
- Eliminate routine calibration and maintenance

### SSF Tape Feeders

8 mm - Triple Lane | 12/16 mm | 24/32 mm | 44 mm | 56 mm



**SSF**  
SERIES

SSF – SIPLACE® compatible tape feeders from Hover-Davis are specifically designed to enhance line operation and productivity.

Each has been designed using the many years of experience we have in component feeder technology. Far from being copies, the SSF range incorporates many unique features that make operation simple, maintenance minimal and cost of ownership the lowest in their class.

The use of stepper motor technology means that tape indexing is fast and repeatable. Component loading is simplified by the introduction of a reverse index tape drive which significantly reduces component loss at set up.

SSF feeders are plug & play compatible and require no modifications to either the machine or placement programs. SSF feeders are 100% user serviceable. Readily available parts and support allow you to enjoy uncomplicated cost of ownership.

As with all Hover-Davis products, SSF tape feeders are supported by our global sales and service network. A comprehensive 2 year warranty package and readily available spare parts ensure peace of mind.

\*Siemens® and "SIPLACE" are registered trademarks of Siemens L&A

Weight	SSF	Siemens
8 mm (Triple Lane)*	2.32 kg (5.10 lbs)	2.56 kg (5.64 lbs)
12/16 mm	1.70 kg (3.74 lbs)	2.44 kg (5.38 lbs)
24/32 mm	2.00 kg (4.40 lbs)	2.72 kg (6.00 lbs)
44 mm	2.27 kg (5.00 lbs)	2.86 kg (6.32 lbs)
56 mm	2.49 kg (5.50 lbs)	2.90 kg (6.38 lbs)

\* Full spectrum component capability – including 0201

### **Machine Compatibility:**

Siemens® SIPLACE® C, F, S, H and D Series

### **Tape Compatibility:**

EIA-481 compliant materials

### **Maximum Pocket Depth:**

14mm

